

329-2014 ADDENDUM 4

NORTH KILDONAN FEEDERMAIN REPLACEMENT

URGENT

PLEASE FORWARD THIS DOCUMENT TO WHOEVER IS IN POSSESSION OF THE BID OPPORTUNITY ISSUED: May 13, 2014 BY: Colin McKinnon TELEPHONE NO. (204) 942-6391

THIS ADDENDUM SHALL BE INCORPORATED INTO THE BID OPPORTUNITY AND SHALL FORM A PART OF THE CONTRACT DOCUMENTS

Please note the following and attached changes, corrections, additions, deletions, information and/or instructions in connection with the Bid Opportunity, and be governed accordingly. Failure to acknowledge receipt of this Addendum in Paragraph 10 of Form A: Bid may render your Bid non-responsive.

PART E - SPECIFICATIONS

Revise: E22.5 Title to read:

Flanged / Compression Sleeve Coupling - F/C Coupling

- Add: E22.10 Dismantling Joint
 - (a) Flange Spool: AWWA Class D Ring Flange, compatible with ANSI Class 125 and 150 bolt circles. For 3" 12" sizes, pipe is Sch 40 ASTM A53. For 14" 72" sizes, ASTM A36 Carbon Steel.
 - (b) End Ring & Body: For 3" 12" sizes, body and end ring are ASTM A536 ductile (nodular) iron meeting or exceeding Grade 65-45-12. For 14" - 72" ASTM A36 Carbon Steel with AWWA C207 Class D flanges. 3" -72" meet the dimensional requirements of ANSI Class 125 and 150 bolt circles.
 - (c) Gaskets: Compounded for water and sewer service in accordance with ASTM D 2000 (ductile iron flange bodies, 3" 12" have flange o-ring gaskets).
 - (d) Bolts & Nuts: High strength low alloy steel bolts and nuts. Steel meets ASTM A588.
 - (e) Coating : Fusion bonded epoxy, NFS 61 certified.
 - (f) Tie-Rods : High strength steel per ASTM A193 B7.